

- ANCHORING:

 ALL SIDE POLE LOCATIONS ANCHORED WITH A SINGLE GUY STRAP AND 2- 1"x42" PINS.

 ALL SIDE POLES SHALL BE ANCHORED WITH 1- 3/4"x36" PIN

 ALL CENTER POLES SHALL BE ANCHORED WITH 2 3/4"x36" PIN

 ALL CORNERS SHALL BE ANCHORED WITH 3 GUY STRAPS, 45" APART; EACH GUY STRAP SHALL HAVE 2- 1"x42" PINS

 FACH GUY LOCATION SHALL HAVE A RESTRAINT CAPACITY OF 13.5KN [3,000 lbf] TO WITHSTAND A 100kp0 [62 Mph] WIND

 EACH 1"x42" PIN SHALL REQUIRE A PULLOUT FORCE OF 13.5KN [3,000 lbf]

 EACH 3/4"x36" PIN SHALL REQUIRE A PULLOUT FORCE OF 9KN [2,000 lbf]


*INSTALLATION CREW MUST ENSURE THAT EACH STRUCTURE/INSTALLATION IS PROPERLY SECURED. SITE CONDITIONS MAY REQUIRE ALTERNATE ANCHORING METHODS OR ADDITIONAL ANCHORING.

DESIGN PARAMETERS:
WIND LOAD: 0.72 kPa [15 psf.]
RAIN LOAD: 0.25 kPa [5.2 psf.]
SNOW LOAD: NONE
SEISMIC LOAD: NOT APPLICABLE

MATERIALS:
FRAME: ANODIZED ALUMINUM TUBING
ELECTROPLATED STEEL TUBING
FABRIC CLADDING: VINYL/POLYESTER FABRIC
FIRE RETARDANT RATING- ULC S-109,
NFPA 701, CALIFORNIA FIRE MARSHAL


AREA: 2400 sqft [223 sqm] WEIGHT: 2428 lbs [1101 kg]

	8' SIDEPOLES	10' SIDEPOLES	
Α	60' [18.29m]	60' [18.29m]	
В	40' [12.19m]	40' [12.19m]	
С	76' [23.16m]	80' [24.38m]	
D	56' [17.07m]	60' [18.29m]	
E	8' [2.43m]	10' [3.01m]	
F	8' [2.43m]	10' [3.01m]	
G	25' [7.62m]	27' [8.23m]	



ITEM NO	. QTY.	PART NO.	DESCRIPTION	WEIGHT [ea.]
1	2	588-5020	TOP END 60' x 20'	310 [141]
2	1	588-5030	TOP MID, 60' x 20'	290 [132]
3	2	588-5040	CENTERPOLE	115 [52.2]
4	20	588-5060	SIDE POLE	12 [5.4]
5	20	588-5061	CROWN & NUT	2 [1]
6	28	588-5080	STAKE BAR	6 [2.8]
7	56	589-1401	STAKE, 1" x 42"	9 [4.1]
8	24	589-1403	STAKE, 3/4" x 36"	7 [3.2]
9	28	588-5080	GUY ASSEMBLY	2 [1]
10	2	588-5050	FLAG POLE	3 [1.4]
11	2	588-5051	FLAG	3 [1.4]
12	10	589-0620	WALL FR WINDOW, 8' x 20'	40 [18.1]

SPECIAL Event SALES



_						
ALL DIMENSIONS IN INCHES						
REV	DESCRIPTION	DRAWN	DATE	CLIE		
0	ISSUED FOR CONST.	RS	20/03/14			
				DES		
AL	CONSULTANT: STRAN CORP, SA PERMIT P10591		•			
CALE		SHEET SIZE				
	1:250	В		DRA		

ESCRIPTION POLE TENT - 40X60

RAWN ND 28/03/14 PT-40060